

# Package: santoku (via r-universe)

July 4, 2024

**Type** Package

**Title** A Versatile Cutting Tool

**Version** 1.0.0

**Maintainer** David Hugh-Jones <davidhughjones@gmail.com>

**Description** A tool for cutting data into intervals. Allows singleton intervals. Always includes the whole range of data by default. Flexible labelling. Convenience functions for cutting by quantiles etc. Handles dates, times, units and other vectors.

**License** MIT + file LICENSE

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.1

**Suggests** bench, bit64, covr, haven, Hmisc, hms, knitr, lubridate, purrr, rmarkdown, scales, stringi, testthat (>= 2.1.0), units, withr, xts, zoo

**LinkingTo** Rcpp

**Depends** R (>= 3.5.0)

**Imports** Rcpp, assertthat, glue, lifecycle, rlang, vctrs

**URL** <https://github.com/hughjonesd/santoku>,  
<https://hughjonesd.github.io/santoku/>

**BugReports** <https://github.com/hughjonesd/santoku/issues>

**VignetteBuilder** knitr

**RdMacros** lifecycle

**Repository** <https://hughjonesd.r-universe.dev>

**RemoteUrl** <https://github.com/hughjonesd/santoku>

**RemoteRef** cran-1.0.0

**RemoteSha** 08a5b9ff805f400c353b6ccdee43dedff5db2755

## Contents

santoku-package . . . . .	2
breaks-class . . . . .	3
brk_default . . . . .	4
brk_manual . . . . .	4
brk_width-for-datetime . . . . .	5
chop . . . . .	6
chop_equally . . . . .	9
chop_evenly . . . . .	11
chop_fn . . . . .	12
chop_mean_sd . . . . .	13
chop_n . . . . .	14
chop_pretty . . . . .	15
chop_proportions . . . . .	16
chop_quantiles . . . . .	17
chop_width . . . . .	19
exactly . . . . .	20
fillet . . . . .	21
lbl_dash . . . . .	22
lbl_discrete . . . . .	23
lbl_endpoints . . . . .	24
lbl_glue . . . . .	26
lbl_intervals . . . . .	28
lbl_midpoints . . . . .	29
lbl_seq . . . . .	30
non-standard-types . . . . .	31
percent . . . . .	32
<b>Index</b>	<b>33</b>

---

santoku-package      *A versatile cutting tool for R*

---

### Description

santoku is a tool for cutting data into intervals. It provides the function `chop()`, which is similar to base R's `cut()` or `Hmisc::cut2()`. `chop(x, breaks)` takes a vector `x` and returns a factor of the same length, coding which interval each element of `x` falls into.

### Details

Here are some advantages of santoku:

- By default, `chop()` always covers the whole range of the data, so you won't get unexpected NA values.

- Unlike `cut()` or `cut2()`, `chop()` can handle single values as well as intervals. For example, `chop(x, breaks = c(1, 2, 2, 3))` will create a separate factor level for values exactly equal to 2.
- Flexible and easy labelling.
- Convenience functions for creating quantile intervals, evenly-spaced intervals or equal-sized groups.
- Convenience functions to quickly tabulate chopped data.
- Can chop numbers, dates, date-times and other objects.

These advantages make `santoku` especially useful for exploratory analysis, where you may not know the range of your data in advance.

To get started, read the vignette:

```
vignette("santoku")
```

For more details, start with the documentation for `chop()`.

### Author(s)

**Maintainer:** David Hugh-Jones <davidhughjones@gmail.com>

Other contributors:

- Daniel Possenriede <possenriede@gmail.com> [contributor]

### See Also

Useful links:

- <https://github.com/hughjonesd/santoku>
- <https://hughjonesd.github.io/santoku/>
- Report bugs at <https://github.com/hughjonesd/santoku/issues>

---

breaks-class

*Class representing a set of intervals*

---

### Description

Class representing a set of intervals

### Usage

```
## S3 method for class 'breaks'  
format(x, ...)
```

```
## S3 method for class 'breaks'  
print(x, ...)
```

```
is.breaks(x, ...)
```

**Arguments**

x	A breaks object
...	Unused

---

brk_default	<i>Create a standard set of breaks</i>
-------------	--

---

**Description**

Create a standard set of breaks

**Usage**

```
brk_default(breaks)
```

**Arguments**

breaks	A numeric vector.
--------	-------------------

**Value**

A function which returns an object of class breaks.

**Examples**

```
chop(1:10, c(2, 5, 8))
chop(1:10, brk_default(c(2, 5, 8)))
```

---

brk_manual	<i>Create a breaks object manually</i>
------------	--

---

**Description**

Create a breaks object manually

**Usage**

```
brk_manual(breaks, left_vec)
```

**Arguments**

breaks	A vector, which must be sorted.
left_vec	A logical vector, the same length as breaks. Specifies whether each break is left-closed or right-closed.

**Details**

All breaks must be closed on exactly one side, like  $\dots, x)$   $[x, \dots$  (left-closed) or  $\dots, x)$   $[x, \dots$  (right-closed).

For example, if `breaks = 1:3` and `left = c(TRUE, FALSE, TRUE)`, then the resulting intervals are

```
T      F      T
[ 1,  2 ] ( 2,  3 )
```

Singleton breaks are created by repeating a number in `breaks`. Singletons must be closed on both sides, so if there is a repeated number at indices  $i, i+1$ , `left[i]` *must* be `TRUE` and `left[i+1]` must be `FALSE`.

**Value**

A function which returns an object of class `breaks`.

**Examples**

```
lbrks <- brk_manual(1:3, rep(TRUE, 3))
chop(1:3, lbrks, extend = FALSE)

rbrks <- brk_manual(1:3, rep(FALSE, 3))
chop(1:3, rbrks, extend = FALSE)

brks_singleton <- brk_manual(
  c(1,  2,  2,  3),
  c(TRUE, TRUE, FALSE, TRUE))

chop(1:3, brks_singleton, extend = FALSE)
```

---

brk\_width-for-datetime

*Equal-width intervals for dates or datetimes*

---

**Description**

`brk_width()` can be used with time interval classes from base R or the `lubridate` package.

**Usage**

```
## S3 method for class 'Duration'
brk_width(width, start)
```

**Arguments**

`width` A scalar [difftime](#), [Period](#) or [Duration](#) object.

`start` A scalar of class [Date](#) or [POSIXct](#). Can be omitted.

## Details

If width is a Period, `lubridate::add_with_rollback()` is used to calculate the widths. This can be useful for e.g. calendar months.

## Examples

```
if (requireNamespace("lubridate")) {
  year2001 <- as.Date("2001-01-01") + 0:364
  tab_width(year2001, months(1),
    labels = lbl_discrete(" to ", fmt = "%e %b %y"))
}
```

---

chop

*Cut data into intervals*

---

## Description

`chop()` cuts `x` into intervals. It returns a `factor` of the same length as `x`, representing which interval contains each element of `x`. `kiru()` is an alias for `chop`. `tab()` calls `chop()` and returns a contingency `table()` from the result.

## Usage

```
chop(
  x,
  breaks,
  labels = lbl_intervals(),
  extend = NULL,
  left = TRUE,
  close_end = TRUE,
  raw = NULL,
  drop = TRUE
)
```

```
kiru(
  x,
  breaks,
  labels = lbl_intervals(),
  extend = NULL,
  left = TRUE,
  close_end = TRUE,
  raw = NULL,
  drop = TRUE
)
```

```
tab(
```

```

x,
breaks,
labels = lbl_intervals(),
extend = NULL,
left = TRUE,
close_end = TRUE,
raw = NULL,
drop = TRUE
)

```

### Arguments

x	A vector.
breaks	A numeric vector of cut-points or a function to create cut-points from x.
labels	A character vector of labels or a function to create labels.
extend	Logical. If TRUE, always extend breaks to +/-Inf. If NULL, extend breaks to min(x) and/or max(x) only if necessary. If NULL, never extend.
left	Logical. Left-closed or right-closed breaks?
close_end	Logical. Close last break at right? (If left is FALSE, close first break at left?)
raw	Logical. Use raw values in labels?
drop	Logical. Drop unused levels from the result?

### Details

x may be a numeric vector, or more generally, any vector which can be compared with < and == (see [Ops](#)). In particular [Date](#) and [date-time](#) objects are supported. Character vectors are supported with a warning.

#### Breaks:

breaks may be a vector or a function.

If it is a vector, breaks gives the break endpoints. Repeated values create singleton intervals. For example breaks = c(1, 3, 3, 5) creates 3 intervals: [1, 3), {3} and (3, 5].

If breaks is a function, it is called with the x, extend, left and close\_end arguments, and should return an object of class breaks. Use brk\_\* functions to create a variety of data-dependent breaks. Names of breaks may be used for labels. See "Labels" below.

#### Options for breaks:

By default, left-closed intervals are created. If left is FALSE, right-closed intervals are created.

If close\_end is TRUE the final break (or first break if left is FALSE) will be closed at both ends. This guarantees that all values x with min(breaks) <= x <= max(breaks) are included in the intervals.

Before version 0.9.0, close\_end was FALSE by default, and also behaved differently with respect to extended breaks: see "Extending intervals" below.

Using [mathematical set notation](#):

- If left is TRUE and close\_end is TRUE, breaks will look like [b1, b2), [b2, b3) ... [b\_n-1, b\_n].

- If `left` is `FALSE` and `close_end` is `TRUE`, breaks will look like `[b1, b2], (b2, b3] ... (b_{n-1}, b_n]`.
- If `left` is `TRUE` and `close_end` is `FALSE`, all breaks will look like `... [b1, b2) ...`.
- If `left` is `FALSE` and `close_end` is `FALSE`, all breaks will look like `... (b1, b2) ...`.

### Extending intervals:

If `extend` is `TRUE`, intervals will be extended to `[-Inf, min(breaks))` and `(max(breaks), Inf]`.

If `extend` is `NULL` (the default), intervals will be extended to `[min(x), min(breaks))` and `(max(breaks), max(x)]`, *only* if necessary – i.e. if elements of `x` would be below or above the unextended breaks.

`close_end` is applied after breaks are extended, i.e. always to the very last or very first break. This is a change from previous behaviour. Up to version 0.8.0, `close_end` was applied to the user-specified intervals, then `extend` was applied. Note that if breaks are extended, then the extended break is always closed anyway.

### Labels:

`labels` may be a character vector. It should have the same length as the (possibly extended) number of intervals. Alternatively, `labels` may be a `lbl_*` function such as `lbl_seq()`.

If `breaks` is a named vector, then non-zero-length names of breaks will be used as labels for the interval starting at the corresponding element. This overrides the `labels` argument (but unnamed breaks will still use `labels`). This feature is **[Experimental]**.

If `labels` is `NULL`, then integer codes will be returned instead of a factor.

If `raw` is `TRUE`, labels will show the actual numbers calculated by breaks. If `raw` is `FALSE` then labels may show other objects, such as quantiles for `chop_quantiles()` and friends, proportions of the range for `chop_proportions()`, or standard deviations for `chop_mean_sd()`.

If `raw` is `NULL` then `lbl_*` functions will use their default (usually `FALSE`). Otherwise, `raw` argument to `chop()` overrides `raw` arguments passed into `lbl_*` functions directly.

### Miscellaneous:

NA values in `x`, and values which are outside the extended endpoints, return NA.

`kiru()` is a synonym for `chop()`. If you load `{tidyr}`, you can use it to avoid confusion with `tidyr::chop()`.

Note that `chop()`, like all of R, uses binary arithmetic. Thus, numbers may not be exactly equal to what you think they should be. There is an example below.

### Value

`chop()` returns a **factor** of the same length as `x`, representing the intervals containing the value of `x`.

`tab()` returns a contingency `table()`.

### See Also

`base::cut()`, `non-standard-types` for chopping objects that aren't numbers.

Other chopping functions: `chop_equally()`, `chop_evenly()`, `chop_fn()`, `chop_mean_sd()`, `chop_n()`, `chop_proportions()`, `chop_quantiles()`, `chop_width()`, `fillet()`



**Examples**

```

chop(1:7, c(2, 4, 6))

chop(1:7, c(2, 4, 6), extend = FALSE)

# Repeat a number for a singleton break:
chop(1:7, c(2, 4, 4, 6))

chop(1:7, c(2, 4, 6), left = FALSE)

chop(1:7, c(2, 4, 6), close_end = FALSE)

chop(1:7, brk_quantiles(c(0.25, 0.75)))

# A single break is fine if `extend` is not `FALSE`:
chop(1:7, 4)

# Floating point inaccuracy:
chop(0.3/3, c(0, 0.1, 0.1, 1), labels = c("< 0.1", "0.1", "> 0.1"))

# -- Labels --

chop(1:7, c(Lowest = 1, Low = 2, Mid = 4, High = 6))

chop(1:7, c(2, 4, 6), labels = c("Lowest", "Low", "Mid", "High"))

chop(1:7, c(2, 4, 6), labels = lbl_dash())

# Mixing names and other labels:
chop(1:7, c("<2" = 1, 2, 4, ">=6" = 6), labels = lbl_dash())

# -- Non-standard types --

chop(as.Date("2001-01-01") + 1:7, as.Date("2001-01-04"))

suppressWarnings(chop(LETTERS[1:7], "D"))

tab(1:10, c(2, 5, 8))

```

---

chop\_equally

*Chop equal-sized groups*


---

**Description**

chop\_equally() chops x into groups with an equal number of elements.

**Usage**

```

chop_equally(
  x,
  groups,
  ...,
  labels = lbl_intervals(),
  left = is.numeric(x),
  close_end = TRUE,
  raw = TRUE
)

brk_equally(groups)

tab_equally(x, groups, ..., left = is.numeric(x), raw = TRUE)

```

**Arguments**

x	A vector.
groups	Number of groups.
...	Passed to <a href="#">chop()</a> .
labels	A character vector of labels or a function to create labels.
left	Logical. Left-closed or right-closed breaks?
close_end	Logical. Close last break at right? (If left is FALSE, close first break at left?)
raw	Logical. Use raw values in labels?

**Details**

`chop_equally()` uses [brk\\_quantiles\(\)](#) under the hood. If `x` has duplicate elements, you may get fewer groups than requested. If so, a warning will be emitted. See the examples.

**Value**

`chop_*` functions return a [factor](#) of the same length as `x`.  
`brk_*` functions return a [function](#) to create breaks.  
`tab_*` functions return a contingency [table\(\)](#).

**See Also**

Other chopping functions: [chop\(\)](#), [chop\\_evenly\(\)](#), [chop\\_fn\(\)](#), [chop\\_mean\\_sd\(\)](#), [chop\\_n\(\)](#), [chop\\_proportions\(\)](#), [chop\\_quantiles\(\)](#), [chop\\_width\(\)](#), [fillet\(\)](#)

**Examples**

```

chop_equally(1:10, 5)

# You can't always guarantee `groups` groups:
dupes <- c(1, 1, 1, 2, 3, 4, 4, 4)
quantile(dupes, 0:4/4)
chop_equally(dupes, 4)

```

---

chop_evenly	<i>Chop into equal-width intervals</i>
-------------	--

---

### Description

chop\_evenly() chops x into intervals intervals of equal width.

### Usage

```
chop_evenly(x, intervals, ..., close_end = TRUE)
```

```
brk_evenly(intervals)
```

```
tab_evenly(x, intervals, ...)
```

### Arguments

x	A vector.
intervals	Integer: number of intervals to create.
...	Passed to <a href="#">chop()</a> .
close_end	Logical. Close last break at right? (If left is FALSE, close first break at left?)

### Details

chop\_evenly() sets close\_end = TRUE by default.

### Value

chop\_\* functions return a [factor](#) of the same length as x.

brk\_\* functions return a [function](#) to create breaks.

tab\_\* functions return a contingency [table\(\)](#).

### See Also

Other chopping functions: [chop\(\)](#), [chop\\_equally\(\)](#), [chop\\_fn\(\)](#), [chop\\_mean\\_sd\(\)](#), [chop\\_n\(\)](#), [chop\\_proportions\(\)](#), [chop\\_quantiles\(\)](#), [chop\\_width\(\)](#), [fillet\(\)](#)

### Examples

```
chop_evenly(0:10, 5)
```

---

 chop\_fn

*Chop using an existing function*


---

**Description**

chop\_fn() is a convenience wrapper: chop\_fn(x, foo, ...) is the same as chop(x, foo(x, ...)).

**Usage**

```
chop_fn(
  x,
  fn,
  ...,
  extend = NULL,
  left = TRUE,
  close_end = TRUE,
  raw = NULL,
  drop = TRUE
)
```

```
brk_fn(fn, ...)
```

```
tab_fn(
  x,
  fn,
  ...,
  extend = NULL,
  left = TRUE,
  close_end = TRUE,
  raw = NULL,
  drop = TRUE
)
```

**Arguments**

x	A vector.
fn	A function which returns a numeric vector of breaks.
...	Further arguments to fn
extend	Logical. If TRUE, always extend breaks to +/-Inf. If NULL, extend breaks to min(x) and/or max(x) only if necessary. If NULL, never extend.
left	Logical. Left-closed or right-closed breaks?
close_end	Logical. Close last break at right? (If left is FALSE, close first break at left?)
raw	Logical. Use raw values in labels?
drop	Logical. Drop unused levels from the result?

**Value**

chop\_\* functions return a [factor](#) of the same length as x.  
 brk\_\* functions return a [function](#) to create breaks.  
 tab\_\* functions return a contingency [table\(\)](#).

**See Also**

Other chopping functions: [chop\(\)](#), [chop\\_equally\(\)](#), [chop\\_evenly\(\)](#), [chop\\_mean\\_sd\(\)](#), [chop\\_n\(\)](#), [chop\\_proportions\(\)](#), [chop\\_quantiles\(\)](#), [chop\\_width\(\)](#), [fillet\(\)](#)

**Examples**

```
if (requireNamespace("scales")) {
  chop_fn(rlnorm(10), scales::breaks_log(5))
  # same as
  # x <- rlnorm(10)
  # chop(x, scales::breaks_log(5)(x))
}
```

---

 chop\_mean\_sd

*Chop by standard deviations*


---

**Description**

Intervals are measured in standard deviations on either side of the mean.

**Usage**

```
chop_mean_sd(x, sds = 1:3, ..., raw = FALSE, sd = deprecated())
```

```
brk_mean_sd(sds = 1:3, sd = deprecated())
```

```
tab_mean_sd(x, sds = 1:3, ..., raw = FALSE)
```

**Arguments**

x	A vector.
sds	Positive numeric vector of standard deviations.
...	Passed to <a href="#">chop()</a> .
raw	Logical. Use raw values in labels?
sd	<b>[Deprecated]</b>

**Details**

In version 0.7.0, these functions changed to specifying sds as a vector. To chop 1, 2 and 3 standard deviations around the mean, write `chop_mean_sd(x, sds = 1:3)` instead of `chop_mean_sd(x, sd = 3)`.

**Value**

chop\_\* functions return a [factor](#) of the same length as x.  
 brk\_\* functions return a [function](#) to create breaks.  
 tab\_\* functions return a contingency [table\(\)](#).

**See Also**

Other chopping functions: [chop\(\)](#), [chop\\_equally\(\)](#), [chop\\_evenly\(\)](#), [chop\\_fn\(\)](#), [chop\\_n\(\)](#), [chop\\_proportions\(\)](#), [chop\\_quantiles\(\)](#), [chop\\_width\(\)](#), [fillet\(\)](#)

**Examples**

```
chop_mean_sd(1:10)
```

```
chop(1:10, brk_mean_sd())
```

```
tab_mean_sd(1:10)
```

---

 chop\_n

---

*Chop into fixed-sized groups*


---

**Description**

chop\_n() creates intervals containing a fixed number of elements.

**Usage**

```
chop_n(x, n, ..., close_end = TRUE, tail = "split")
```

```
brk_n(n, tail = "split")
```

```
tab_n(x, n, ..., tail = "split")
```

**Arguments**

x	A vector.
n	Integer. Number of elements in each interval.
...	Passed to <a href="#">chop()</a> .
close_end	Logical. Close last break at right? (If left is FALSE, close first break at left?)
tail	String. What to do if the final interval has fewer than n elements? "split" to keep it separate. "merge" to merge it with the neighbouring interval.

**Details**

The algorithm guarantees that intervals contain no more than `n` elements, so long as there are no duplicates in `x` and `tail = "split"`. It also guarantees that intervals contain no fewer than `n` elements, except possibly the last interval (or first interval if `left` is `FALSE`).

To ensure that all intervals contain at least `n` elements (so long as there are at least `n` elements in `x`!) set `tail = "merge"`.

If `tail = "split"` and there are intervals containing duplicates with more than `n` elements, a warning is given.

**Value**

`chop_*` functions return a [factor](#) of the same length as `x`.

`brk_*` functions return a [function](#) to create breaks.

`tab_*` functions return a contingency [table\(\)](#).

**See Also**

Other chopping functions: [chop\(\)](#), [chop\\_equally\(\)](#), [chop\\_evenly\(\)](#), [chop\\_fn\(\)](#), [chop\\_mean\\_sd\(\)](#), [chop\\_proportions\(\)](#), [chop\\_quantiles\(\)](#), [chop\\_width\(\)](#), [fillet\(\)](#)

**Examples**

```
chop_n(1:10, 5)

chop_n(1:5, 2)
chop_n(1:5, 2, tail = "merge")

# too many duplicates
x <- rep(1:2, each = 3)
chop_n(x, 2)

tab_n(1:10, 5)

# fewer elements in one group
tab_n(1:10, 4)
```

---

 chop\_pretty

*Chop using pretty breakpoints*


---

**Description**

`chop_pretty()` uses [base::pretty\(\)](#) to calculate breakpoints which are 1, 2 or 5 times a power of 10. These look nice in graphs.

**Usage**

```
chop_pretty(x, n = 5, ...)
```

```
brk_pretty(n = 5, ...)
```

```
tab_pretty(x, n = 5, ...)
```

**Arguments**

x	A vector.
n	Positive integer passed to <code>base::pretty()</code> . How many intervals to chop into?
...	Passed to <code>chop()</code> by <code>chop_pretty()</code> and <code>tab_pretty()</code> ; passed to <code>base::pretty()</code> by <code>brk_pretty()</code> .

**Details**

`base::pretty()` tries to return  $n+1$  breakpoints, i.e.  $n$  intervals, but note that this is not guaranteed. There are methods for Date and POSIXct objects.

For fine-grained control over `base::pretty()` parameters, use `chop(x, brk_pretty(...))`.

**Value**

`chop_*` functions return a **factor** of the same length as `x`.

`brk_*` functions return a **function** to create breaks.

`tab_*` functions return a contingency **table()**.

**Examples**

```
chop_pretty(1:10)
```

```
chop(1:10, brk_pretty(n = 5, high.u.bias = 0))
```

```
tab_pretty(1:10)
```

---

```
chop_proportions
```

```
Chop into proportions of the range of x
```

---

**Description**

`chop_proportions()` chops `x` into proportions of its range, excluding infinite values.

**Usage**

```
chop_proportions(x, proportions, ..., raw = TRUE)
```

```
brk_proportions(proportions)
```

```
tab_proportions(x, proportions, ..., raw = TRUE)
```



**Arguments**

x	A vector.
proportions	Numeric vector between 0 and 1: proportions of x's range. If proportions has names, these will be used for labels.
...	Passed to <code>chop()</code> .
raw	Logical. Use raw values in labels?

**Details**

By default, labels show the raw numeric endpoints. To label intervals by the proportions, use `raw = FALSE`.

**Value**

`chop_*` functions return a `factor` of the same length as `x`.  
`brk_*` functions return a `function` to create breaks.  
`tab_*` functions return a contingency `table()`.

**See Also**

Other chopping functions: `chop()`, `chop_equally()`, `chop_evenly()`, `chop_fn()`, `chop_mean_sd()`, `chop_n()`, `chop_quantiles()`, `chop_width()`, `fillet()`

**Examples**

```
chop_proportions(0:10, c(0.2, 0.8))
chop_proportions(0:10, c(Low = 0, Mid = 0.2, High = 0.8))
```

---

chop_quantiles	<i>Chop by quantiles</i>
----------------	--------------------------

---

**Description**

`chop_quantiles()` chops data by quantiles. `chop_deciles()` is a convenience function which chops into deciles.

**Usage**

```
chop_quantiles(
  x,
  probs,
  ...,
  left = is.numeric(x),
  raw = FALSE,
  weights = NULL
)
```

```
chop_deciles(x, ...)
```

```
brk_quantiles(probs, ..., weights = NULL)
```

```
tab_quantiles(x, probs, ..., left = is.numeric(x), raw = FALSE)
```

```
tab_deciles(x, ...)
```

### Arguments

<code>x</code>	A vector.
<code>probs</code>	A vector of probabilities for the quantiles. If <code>probs</code> has names, these will be used for labels.
<code>...</code>	For <code>chop_quantiles</code> , passed to <code>chop()</code> . For <code>brk_quantiles()</code> , passed to <code>stats::quantile()</code> or <code>Hmisc::wtd.quantile()</code> .
<code>left</code>	Logical. Left-closed or right-closed breaks?
<code>raw</code>	Logical. Use raw values in labels?
<code>weights</code>	NULL or numeric vector of same length as <code>x</code> . If not NULL, <code>Hmisc::wtd.quantile()</code> is used to calculate weighted quantiles.

### Details

For non-numeric `x`, `left` is set to `FALSE` by default. This works better for calculating "type 1" quantiles, since they round down. See `stats::quantile()`.

If `x` contains duplicates, consecutive quantiles may be the same number so that some intervals get merged.

### Value

`chop_*` functions return a `factor` of the same length as `x`.

`brk_*` functions return a `function` to create breaks.

`tab_*` functions return a contingency `table()`.

### See Also

Other chopping functions: `chop()`, `chop_equally()`, `chop_evenly()`, `chop_fn()`, `chop_mean_sd()`, `chop_n()`, `chop_proportions()`, `chop_width()`, `fillet()`

### Examples

```
chop_quantiles(1:10, 1:3/4)
```

```
chop_quantiles(1:10, c(Q1 = 0, Q2 = 0.25, Q3 = 0.5, Q4 = 0.75))
```

```
chop(1:10, brk_quantiles(1:3/4))
```

```
chop_deciles(1:10)
```

```
# to label by the quantiles themselves:
chop_quantiles(1:10, 1:3/4, raw = TRUE)

# duplicates:
tab_quantiles(c(1, 1, 1, 2, 3), 1:5/5)

set.seed(42)
tab_quantiles(rnorm(100), probs = 1:3/4, raw = TRUE)
```

---

chop_width	<i>Chop into fixed-width intervals</i>
------------	--

---

### Description

chop\_width() chops x into intervals of fixed width.

### Usage

```
chop_width(x, width, start, ..., left = sign(width) > 0)

brk_width(width, start)

## Default S3 method:
brk_width(width, start)

tab_width(x, width, start, ..., left = sign(width) > 0)
```

### Arguments

x	A vector.
width	Width of intervals.
start	Starting point for intervals. By default the smallest finite x (largest if width is negative).
...	Passed to <a href="#">chop()</a> .
left	Logical. Left-closed or right-closed breaks?

### Details

If width is negative, chop\_width() sets left = FALSE and intervals will go downwards from start.

### Value

chop\_\* functions return a [factor](#) of the same length as x.  
brk\_\* functions return a [function](#) to create breaks.  
tab\_\* functions return a contingency [table\(\)](#).

**See Also**

[brk\\_width-for-datetime](#)

Other chopping functions: [chop\(\)](#), [chop\\_equally\(\)](#), [chop\\_evenly\(\)](#), [chop\\_fn\(\)](#), [chop\\_mean\\_sd\(\)](#), [chop\\_n\(\)](#), [chop\\_proportions\(\)](#), [chop\\_quantiles\(\)](#), [fillet\(\)](#)

**Examples**

```
chop_width(1:10, 2)

chop_width(1:10, 2, start = 0)

chop_width(1:9, -2)

chop(1:10, brk_width(2, 0))

tab_width(1:10, 2, start = 0)
```

---

exactly

*Define singleton intervals explicitly*

---

**Description**

`exactly()` duplicates its input. It lets you define singleton intervals like this: `chop(x, c(1, exactly(2), 3))`. This is the same as `chop(x, c(1, 2, 2, 3))` but conveys your intent more clearly.

**Usage**

```
exactly(x)
```

**Arguments**

`x`                    A numeric vector.

**Value**

The same as `rep(x, each = 2)`.

**Examples**

```
chop(1:10, c(2, exactly(5), 8))

# same:
chop(1:10, c(2, 5, 5, 8))
```

---

`fillet`*Chop data precisely (for programmers)*

---

### Description

`fillet()` calls `chop()` with `extend = FALSE` and `drop = FALSE`. This ensures that you get only the breaks and labels you ask for. When programming, consider using `fillet()` instead of `chop()`.

### Usage

```
fillet(  
  x,  
  breaks,  
  labels = lbl_intervals(),  
  left = TRUE,  
  close_end = TRUE,  
  raw = NULL  
)
```

### Arguments

<code>x</code>	A vector.
<code>breaks</code>	A numeric vector of cut-points or a function to create cut-points from <code>x</code> .
<code>labels</code>	A character vector of labels or a function to create labels.
<code>left</code>	Logical. Left-closed or right-closed breaks?
<code>close_end</code>	Logical. Close last break at right? (If <code>left</code> is <code>FALSE</code> , close first break at left?)
<code>raw</code>	Logical. Use raw values in labels?

### Value

`fillet()` returns a [factor](#) of the same length as `x`, representing the intervals containing the value of `x`.

### See Also

Other chopping functions: [chop\(\)](#), [chop\\_equally\(\)](#), [chop\\_evenly\(\)](#), [chop\\_fn\(\)](#), [chop\\_mean\\_sd\(\)](#), [chop\\_n\(\)](#), [chop\\_proportions\(\)](#), [chop\\_quantiles\(\)](#), [chop\\_width\(\)](#)

### Examples

```
fillet(1:10, c(2, 5, 8))
```

---

lbl_dash	<i>Label chopped intervals like 1-4, 4-5, ...</i>
----------	---

---

### Description

This label style is user-friendly, but doesn't distinguish between left- and right-closed intervals. It's good for continuous data where you don't expect points to be exactly on the breaks.

### Usage

```
lbl_dash(
  symbol = em_dash(),
  fmt = NULL,
  single = "{l}",
  first = NULL,
  last = NULL,
  raw = FALSE
)
```

### Arguments

symbol	String: symbol to use for the dash.
fmt	String, list or function. A format for break endpoints.
single	Glue string: label for singleton intervals. See <a href="#">lbl_glue()</a> for details.
first	Glue string: override label for the first category. Write e.g. <code>first = "&lt;{r}"</code> to create a label like " <code>&lt;18</code> ". See <a href="#">lbl_glue()</a> for details.
last	String: override label for the last category. Write e.g. <code>last = "&gt;{l}"</code> to create a label like " <code>&gt;65</code> ". See <a href="#">lbl_glue()</a> for details.
raw	<b>[Deprecated]</b> . Use the raw argument to <a href="#">chop()</a> instead.

### Details

If you don't want unicode output, use `lbl_dash("-")`.

### Value

A function that creates a vector of labels.

### Formatting endpoints

If `fmt` is not `NULL` then it is used to format the endpoints.

- If `fmt` is a string, then numeric endpoints will be formatted by `sprintf(fmt, breaks)`; other endpoints, e.g. [Date](#) objects, will be formatted by `format(breaks, fmt)`.
- If `fmt` is a list, then it will be used as arguments to [format](#).
- If `fmt` is a function, it should take a vector of numbers (or other objects that can be used as breaks) and return a character vector. It may be helpful to use functions from the `{scales}` package, e.g. `scales::label_comma()`.

**See Also**

Other labelling functions: [lbl\\_discrete\(\)](#), [lbl\\_endpoints\(\)](#), [lbl\\_glue\(\)](#), [lbl\\_intervals\(\)](#), [lbl\\_manual\(\)](#), [lbl\\_midpoints\(\)](#), [lbl\\_seq\(\)](#)

**Examples**

```
chop(1:10, c(2, 5, 8), lbl_dash())

chop(1:10, c(2, 5, 8), lbl_dash(" to ", fmt = "%.1f"))

chop(1:10, c(2, 5, 8), lbl_dash(first = "<{r}"))

pretty <- function(x) prettyNum(x, big.mark = ",", digits = 1)
chop(runif(10) * 10000, c(3000, 7000), lbl_dash(" to ", fmt = pretty))
```

---

 lbl\_discrete

*Label discrete data*


---

**Description**

`lbl_discrete()` creates labels for discrete data, such as integers. For example, breaks `c(1, 3, 4, 6, 7)` are labelled: "1-2", "3", "4-5", "6-7".

**Usage**

```
lbl_discrete(
  symbol = em_dash(),
  unit = 1,
  fmt = NULL,
  single = NULL,
  first = NULL,
  last = NULL
)
```

**Arguments**

<code>symbol</code>	String: symbol to use for the dash.
<code>unit</code>	Minimum difference between distinct values of data. For integers, 1.
<code>fmt</code>	String, list or function. A format for break endpoints.
<code>single</code>	Glue string: label for singleton intervals. See <a href="#">lbl_glue()</a> for details.
<code>first</code>	Glue string: override label for the first category. Write e.g. <code>first = "&lt;{r}"</code> to create a label like "<18". See <a href="#">lbl_glue()</a> for details.
<code>last</code>	String: override label for the last category. Write e.g. <code>last = "&gt;{1}"</code> to create a label like ">65". See <a href="#">lbl_glue()</a> for details.

**Details**

No check is done that the data are discrete-valued. If they are not, then these labels may be misleading. Here, discrete-valued means that if  $x < y$ , then  $x \leq y - \text{unit}$ .

Be aware that Date objects may have non-integer values. See [Date](#).

**Value**

A function that creates a vector of labels.

**Formatting endpoints**

If `fmt` is not `NULL` then it is used to format the endpoints.

- If `fmt` is a string, then numeric endpoints will be formatted by `sprintf(fmt, breaks)`; other endpoints, e.g. [Date](#) objects, will be formatted by `format(breaks, fmt)`.
- If `fmt` is a list, then it will be used as arguments to [format](#).
- If `fmt` is a function, it should take a vector of numbers (or other objects that can be used as breaks) and return a character vector. It may be helpful to use functions from the `{scales}` package, e.g. `scales::label_comma()`.

**See Also**

Other labelling functions: [lbl\\_dash\(\)](#), [lbl\\_endpoints\(\)](#), [lbl\\_glue\(\)](#), [lbl\\_intervals\(\)](#), [lbl\\_manual\(\)](#), [lbl\\_midpoints\(\)](#), [lbl\\_seq\(\)](#)

**Examples**

```
tab(1:7, c(1, 3, 5), lbl_discrete())

tab(1:7, c(3, 5), lbl_discrete(first = "<= {r}"))

tab(1:7 * 1000, c(1, 3, 5) * 1000, lbl_discrete(unit = 1000))

# Misleading labels for non-integer data
chop(2.5, c(1, 3, 5), lbl_discrete())
```

---

lbl\_endpoints

*Label chopped intervals by their left or right endpoints*

---

**Description**

This is useful when the left endpoint unambiguously indicates the interval. In other cases it may give errors due to duplicate labels.



**Usage**

```

lbl_endpoints(
  left = TRUE,
  fmt = NULL,
  single = NULL,
  first = NULL,
  last = NULL,
  raw = FALSE
)

```

```

lbl_endpoint(fmt = NULL, raw = FALSE, left = TRUE)

```

**Arguments**

left	Flag. Use left endpoint or right endpoint?
fmt	String, list or function. A format for break endpoints.
single	Glue string: label for singleton intervals. See <a href="#">lbl_glue()</a> for details.
first	Glue string: override label for the first category. Write e.g. <code>first = "&lt;{r}"</code> to create a label like "<18". See <a href="#">lbl_glue()</a> for details.
last	String: override label for the last category. Write e.g. <code>last = "&gt;{l}"</code> to create a label like ">65". See <a href="#">lbl_glue()</a> for details.
raw	<b>[Deprecated]</b> . Use the raw argument to <a href="#">chop()</a> instead.

**Details**

`lbl_endpoint()` is **[Defunct]** and gives an error since `santoku 1.0.0`.

**Value**

A function that creates a vector of labels.

**Formatting endpoints**

If `fmt` is not `NULL` then it is used to format the endpoints.

- If `fmt` is a string, then numeric endpoints will be formatted by `sprintf(fmt, breaks)`; other endpoints, e.g. [Date](#) objects, will be formatted by `format(breaks, fmt)`.
- If `fmt` is a list, then it will be used as arguments to [format](#).
- If `fmt` is a function, it should take a vector of numbers (or other objects that can be used as breaks) and return a character vector. It may be helpful to use functions from the `{scales}` package, e.g. `scales::label_comma()`.

**See Also**

Other labelling functions: [lbl\\_dash\(\)](#), [lbl\\_discrete\(\)](#), [lbl\\_glue\(\)](#), [lbl\\_intervals\(\)](#), [lbl\\_manual\(\)](#), [lbl\\_midpoints\(\)](#), [lbl\\_seq\(\)](#)

**Examples**

```

chop(1:10, c(2, 5, 8), lbl_endpoints(left = TRUE))
chop(1:10, c(2, 5, 8), lbl_endpoints(left = FALSE))
if (requireNamespace("lubridate")) {
  tab_width(
    as.Date("2000-01-01") + 0:365,
    months(1),
    labels = lbl_endpoints(fmt = "%b")
  )
}

## Not run:
# This gives breaks `[1, 2) [2, 3) {3}` which lead to
# duplicate labels `2", "3", "3":
chop(1:3, 1:3, lbl_endpoints(left = FALSE))

## End(Not run)

```

---

 lbl\_glue

*Label chopped intervals using the glue package*


---

**Description**

Use "{l}" and "{r}" to show the left and right endpoints of the intervals.

**Usage**

```

lbl_glue(
  label,
  fmt = NULL,
  single = NULL,
  first = NULL,
  last = NULL,
  raw = FALSE,
  ...
)

```

**Arguments**

label	A glue string passed to <code>glue::glue()</code> .
fmt	String, list or function. A format for break endpoints.
single	Glue string: label for singleton intervals. See <code>lbl_glue()</code> for details.
first	Glue string: override label for the first category. Write e.g. <code>first = "&lt;{r}"</code> to create a label like "<18". See <code>lbl_glue()</code> for details.
last	String: override label for the last category. Write e.g. <code>last = "&gt;{l}"</code> to create a label like ">65". See <code>lbl_glue()</code> for details.
raw	<b>[Deprecated]</b> . Use the <code>raw</code> argument to <code>chop()</code> instead.
...	Further arguments passed to <code>glue::glue()</code> .

## Details

The following variables are available in the glue string:

- `l` is a character vector of left endpoints of intervals.
- `r` is a character vector of right endpoints of intervals.
- `l_closed` is a logical vector. Elements are TRUE when the left endpoint is closed.
- `r_closed` is a logical vector, TRUE when the right endpoint is closed.

Endpoints will be formatted by `fmt` before being passed to `glue()`.

## Value

A function that creates a vector of labels.

## Formatting endpoints

If `fmt` is not NULL then it is used to format the endpoints.

- If `fmt` is a string, then numeric endpoints will be formatted by `sprintf(fmt, breaks)`; other endpoints, e.g. [Date](#) objects, will be formatted by `format(breaks, fmt)`.
- If `fmt` is a list, then it will be used as arguments to [format](#).
- If `fmt` is a function, it should take a vector of numbers (or other objects that can be used as breaks) and return a character vector. It may be helpful to use functions from the `{scales}` package, e.g. `scales::label_comma()`.

## See Also

Other labelling functions: [lbl\\_dash\(\)](#), [lbl\\_discrete\(\)](#), [lbl\\_endpoints\(\)](#), [lbl\\_intervals\(\)](#), [lbl\\_manual\(\)](#), [lbl\\_midpoints\(\)](#), [lbl\\_seq\(\)](#)

## Examples

```
tab(1:10, c(1, 3, 3, 7),
    labels = lbl_glue("{l} to {r}", single = "Exactly {l}"))

tab(1:10 * 1000, c(1, 3, 5, 7) * 1000,
    labels = lbl_glue("{l}-{r}",
                      fmt = function(x) prettyNum(x, big.mark=','))

# reproducing lbl_intervals():
interval_left <- "{ifelse(l_closed, '[', '(')}"
interval_right <- "{ifelse(r_closed, ']', ')'}"
glue_string <- paste0(interval_left, "{l}", ", ", "{r}", interval_right)
tab(1:10, c(1, 3, 3, 7), labels = lbl_glue(glue_string, single = "{{{l}}}")
```

---

 lbl\_intervals

*Label chopped intervals using set notation*


---

### Description

These labels are the most exact, since they show you whether intervals are "closed" or "open", i.e. whether they include their endpoints.

### Usage

```
lbl_intervals(
  fmt = NULL,
  single = "{{{1}}}",
  first = NULL,
  last = NULL,
  raw = FALSE
)
```

### Arguments

fmt	String, list or function. A format for break endpoints.
single	Glue string: label for singleton intervals. See <a href="#">lbl_glue()</a> for details.
first	Glue string: override label for the first category. Write e.g. first = "<{r}" to create a label like "<18". See <a href="#">lbl_glue()</a> for details.
last	String: override label for the last category. Write e.g. last = ">{1}" to create a label like ">65". See <a href="#">lbl_glue()</a> for details.
raw	<b>[Deprecated]</b> . Use the raw argument to <a href="#">chop()</a> instead.

### Details

Mathematical set notation looks like this:

- $[a, b]$ : all numbers  $x$  where  $a \leq x \leq b$ ;
- $(a, b)$ : all numbers where  $a < x < b$ ;
- $[a, b)$ : all numbers where  $a \leq x < b$ ;
- $(a, b]$ : all numbers where  $a < x \leq b$ ;
- $\{a\}$ : just the number  $a$  exactly.

### Value

A function that creates a vector of labels.

## Formatting endpoints

If `fmt` is not `NULL` then it is used to format the endpoints.

- If `fmt` is a string, then numeric endpoints will be formatted by `sprintf(fmt, breaks)`; other endpoints, e.g. `Date` objects, will be formatted by `format(breaks, fmt)`.
- If `fmt` is a list, then it will be used as arguments to `format`.
- If `fmt` is a function, it should take a vector of numbers (or other objects that can be used as breaks) and return a character vector. It may be helpful to use functions from the `{scales}` package, e.g. `scales::label_comma()`.

## See Also

Other labelling functions: `lbl_dash()`, `lbl_discrete()`, `lbl_endpoints()`, `lbl_glue()`, `lbl_manual()`, `lbl_midpoints()`, `lbl_seq()`

## Examples

```
tab(-10:10, c(-3, 0, 0, 3),
    labels = lbl_intervals())

tab(-10:10, c(-3, 0, 0, 3),
    labels = lbl_intervals(fmt = list(nsmall = 1)))

tab_evenly(runif(20), 10,
    labels = lbl_intervals(fmt = percent))
```

---

lbl_midpoints	<i>Label chopped intervals by their midpoints</i>
---------------	---

---

## Description

This uses the midpoint of each interval for its label.

## Usage

```
lbl_midpoints(
  fmt = NULL,
  single = NULL,
  first = NULL,
  last = NULL,
  raw = FALSE
)
```

**Arguments**

fmt	String, list or function. A format for break endpoints.
single	Glue string: label for singleton intervals. See <a href="#">lbl_glue()</a> for details.
first	Glue string: override label for the first category. Write e.g. <code>first = "&lt;{r}"</code> to create a label like "<18". See <a href="#">lbl_glue()</a> for details.
last	String: override label for the last category. Write e.g. <code>last = "&gt;{1}"</code> to create a label like ">65". See <a href="#">lbl_glue()</a> for details.
raw	<b>[Deprecated]</b> . Use the raw argument to <a href="#">chop()</a> instead.

**Value**

A function that creates a vector of labels.

**Formatting endpoints**

If `fmt` is not `NULL` then it is used to format the endpoints.

- If `fmt` is a string, then numeric endpoints will be formatted by `sprintf(fmt, breaks)`; other endpoints, e.g. [Date](#) objects, will be formatted by `format(breaks, fmt)`.
- If `fmt` is a list, then it will be used as arguments to [format](#).
- If `fmt` is a function, it should take a vector of numbers (or other objects that can be used as breaks) and return a character vector. It may be helpful to use functions from the `{scales}` package, e.g. [scales::label\\_comma\(\)](#).

**See Also**

Other labelling functions: [lbl\\_dash\(\)](#), [lbl\\_discrete\(\)](#), [lbl\\_endpoints\(\)](#), [lbl\\_glue\(\)](#), [lbl\\_intervals\(\)](#), [lbl\\_manual\(\)](#), [lbl\\_seq\(\)](#)

**Examples**

```
chop(1:10, c(2, 5, 8), lbl_midpoints())
```

---

lbl\_seq

*Label chopped intervals in sequence*

---

**Description**

`lbl_seq()` labels intervals sequentially, using numbers or letters.

**Usage**

```
lbl_seq(start = "a")
```

**Arguments**

start                   String. A template for the sequence. See below.

**Details**

start shows the first element of the sequence. It must contain exactly *one* character out of the set "a", "A", "i", "I" or "1". For later elements:

- "a" will be replaced by "a", "b", "c", ...
- "A" will be replaced by "A", "B", "C", ...
- "i" will be replaced by lower-case Roman numerals "i", "ii", "iii", ...
- "I" will be replaced by upper-case Roman numerals "I", "II", "III", ...
- "1" will be replaced by numbers "1", "2", "3", ...

Other characters will be retained as-is.

**Value**

A function that creates a vector of labels.

**See Also**

Other labelling functions: [lbl\\_dash\(\)](#), [lbl\\_discrete\(\)](#), [lbl\\_endpoints\(\)](#), [lbl\\_glue\(\)](#), [lbl\\_intervals\(\)](#), [lbl\\_manual\(\)](#), [lbl\\_midpoints\(\)](#)

**Examples**

```
chop(1:10, c(2, 5, 8), lbl_seq())
chop(1:10, c(2, 5, 8), lbl_seq("i."))
chop(1:10, c(2, 5, 8), lbl_seq("(A)"))
```

---

non-standard-types      *Tips for chopping non-standard types*

---

**Description**

Santoku can handle many non-standard types.

**Details**

- If objects can be compared using <, == etc. then they should be choppable.
- Objects which can't be converted to numeric are handled within R code, which may be slower.
- Character x and breaks are chopped with a warning.
- If x and breaks are not the same type, they should be able to be cast to the same type, usually using `vctrs::vec_cast_common()`.
- Not all chopping operations make sense, for example, [chop\\_mean\\_sd\(\)](#) on a character vector.
- For indexed objects such as `stats::ts()` objects, indices will be dropped from the result.
- If you get errors, try setting `extend = FALSE` (but also file a bug report).
- To request support for a type, open an issue on Github.

**See Also**

brk-width-for-Datetime

---

percent

*Simple percentage formatter*

---

**Description**

percent() formats x as a percentage. For a wider range of formatters, consider the [scales package](#).

**Usage**

```
percent(x)
```

**Arguments**

x                    Numeric values.

**Value**

x formatted as a percent.

**Examples**

```
percent(0.5)
```



# Index

## \* **chopping functions**

- chop, 6
- chop\_equally, 9
- chop\_evenly, 11
- chop\_fn, 12
- chop\_mean\_sd, 13
- chop\_n, 14
- chop\_proportions, 16
- chop\_quantiles, 17
- chop\_width, 19
- fillet, 21

## \* **labelling functions**

- lbl\_dash, 22
- lbl\_discrete, 23
- lbl\_endpoints, 24
- lbl\_glue, 26
- lbl\_intervals, 28
- lbl\_midpoints, 29
- lbl\_seq, 30

- base::cut(), 8
- base::pretty(), 15, 16
- breaks-class, 3
- brk\_default, 4
- brk\_equally (chop\_equally), 9
- brk\_evenly (chop\_evenly), 11
- brk\_fn (chop\_fn), 12
- brk\_manual, 4
- brk\_mean\_sd (chop\_mean\_sd), 13
- brk\_n (chop\_n), 14
- brk\_pretty (chop\_pretty), 15
- brk\_proportions (chop\_proportions), 16
- brk\_quantiles (chop\_quantiles), 17
- brk\_quantiles(), 10
- brk\_width (chop\_width), 19
- brk\_width-for-datetime, 5, 20
- brk\_width.Duration
  - (brk\_width-for-datetime), 5

chop, 6, 10, 11, 13–15, 17, 18, 20, 21

- chop(), 2, 3, 10, 11, 13, 14, 16–19, 21, 22, 25, 26, 28, 30
- chop\_deciles (chop\_quantiles), 17
- chop\_equally, 8, 9, 11, 13–15, 17, 18, 20, 21
- chop\_evenly, 8, 10, 11, 13–15, 17, 18, 20, 21
- chop\_fn, 8, 10, 11, 12, 14, 15, 17, 18, 20, 21
- chop\_mean\_sd, 8, 10, 11, 13, 13, 15, 17, 18, 20, 21
- chop\_mean\_sd(), 8, 31
- chop\_n, 8, 10, 11, 13, 14, 14, 17, 18, 20, 21
- chop\_pretty, 15
- chop\_proportions, 8, 10, 11, 13–15, 16, 18, 20, 21
- chop\_proportions(), 8
- chop\_quantiles, 8, 10, 11, 13–15, 17, 17, 20, 21
- chop\_quantiles(), 8
- chop\_width, 8, 10, 11, 13–15, 17, 18, 19, 21
- cut(), 2

- Date, 5, 7, 22, 24, 25, 27, 29, 30
- date-time, 7
- difftime, 5
- Duration, 5

exactly, 20

- factor, 6, 8, 10, 11, 13–19, 21
- fillet, 8, 10, 11, 13–15, 17, 18, 20, 21
- format, 22, 24, 25, 27, 29, 30
- format.breaks (breaks-class), 3
- function, 10, 11, 13–19

glue::glue(), 26

Hmisc::wtd.quantile(), 18

is.breaks (breaks-class), 3

kiru (chop), 6

lbl\_dash, [22](#), [24](#), [25](#), [27](#), [29–31](#)  
lbl\_discrete, [23](#), [23](#), [25](#), [27](#), [29–31](#)  
lbl\_endpoint (lbl\_endpoints), [24](#)  
lbl\_endpoints, [23](#), [24](#), [24](#), [27](#), [29–31](#)  
lbl\_glue, [23–25](#), [26](#), [29–31](#)  
lbl\_glue(), [22](#), [23](#), [25](#), [26](#), [28](#), [30](#)  
lbl\_intervals, [23–25](#), [27](#), [28](#), [30](#), [31](#)  
lbl\_manual, [23–25](#), [27](#), [29–31](#)  
lbl\_midpoints, [23–25](#), [27](#), [29](#), [29](#), [31](#)  
lbl\_seq, [23–25](#), [27](#), [29](#), [30](#), [30](#)  
lbl\_seq(), [8](#)  
lubridate::add\_with\_rollback(), [6](#)  
  
mathematical set notation, [7](#)  
  
non-standard-types, [31](#)  
  
Ops, [7](#)  
  
percent, [32](#)  
Period, [5](#)  
POSIXct, [5](#)  
print.breaks (breaks-class), [3](#)  
  
santoku (santoku-package), [2](#)  
santoku-package, [2](#)  
scales::label\_comma(), [22](#), [24](#), [25](#), [27](#), [29](#),  
[30](#)  
stats::quantile(), [18](#)  
stats::ts(), [31](#)  
  
tab (chop), [6](#)  
tab\_deciles (chop\_quantiles), [17](#)  
tab\_equally (chop\_equally), [9](#)  
tab\_evenly (chop\_evenly), [11](#)  
tab\_fn (chop\_fn), [12](#)  
tab\_mean\_sd (chop\_mean\_sd), [13](#)  
tab\_n (chop\_n), [14](#)  
tab\_pretty (chop\_pretty), [15](#)  
tab\_proportions (chop\_proportions), [16](#)  
tab\_quantiles (chop\_quantiles), [17](#)  
tab\_width (chop\_width), [19](#)  
table(), [6](#), [8](#), [10](#), [11](#), [13–19](#)  
  
vctrs::vec\_cast\_common(), [31](#)